

Remote Monitoring System



	Signal	Data	Control
Door Alarm	✓		
Fire / Smoke Alarm	✓		
Water Leak Alarm	✓		
Temperature		✓	
Humidity		✓	
Power Consumption		✓	
PDU		✓	
Space Usage		✓	
Asset Management System		✓	
A.C. / Cooling			✓
Door Access			✓
Equipment			✓

Stay connected



[longxing telecom](#)

[www.lxtelecom.com](#)

Anju Road, Beilun District, Ningbo, China

+86 574 87917627
+86 574 87908188



Ver: 070618

Scan to download catalog

Attention:
Specifications published here are current as of the date of publication of this document.
Because we are continuously improving our products, LongXing reserves the right to change specifications
without prior notice. At any time, you may verify product specifications by contacting LongXing.



CabiCentre

All in one mini data centre solution

An expert designed, pre-configured, self-contained and factory tested all-in-one cabinet that provides solution for edge applications and small business IT requirements.




CabiCentre - Benefits

	Typical Edge Applications	CabiCentre
Renovation	Required	Minimum
Design	Required in advance	Proven solution
Installation	Complicated with different suppliers	Plug & play
Cabling	Hard to organise	Factory settled
Set Up Time	15-20 days	1 day
Floor Area	10-20 sqm	1.38 sqm
Power Supply	Separate tower UPS + battery stand	Pre-installed and wired
Power Distribution	Low intergation, wall mount	Integrated with lightning protection
Cooling	High	Minimal
Monitoring	Complex for integrating all systems	Integrated and tested
Appearance	Neat & organized	Standard network cabinet looking
Service	By different suppliers	LongXing



Key Components



Technical Specifications

Parameter	CabiCentre
Dimensions (H*W*D):	2200mm*600mm*1100mm
Usable Rack Space:	27U
Air Conditioner:	Integrated
Floor Area (incl. service space):	1.38m ²
Color:	Black (RAL 9005)
Display:	10.1" Touch Screen
Display Languages:	English / Chinese
Auto LED Lighting:	2, Front & Rear
UPS Capacity:	6kVA
UPS Backup Time:	20-60 minutes @ 3.5kW
System Capacity:	3.5kW
System Input Requirement:	Single Phase 110V/220 V-240 V
Power Distribution Units (PDU):	16A input, IEC
Lightning Protection / Surge Suppression:	Level 3, 20kA
Cooling Capacity:	3.5kW
Emergency Fan:	Optional
System Management (UPS/Cooling/PDU):	Yes
Temperature Sensor:	6
Water Leak Detector:	1
Door Access Sensor:	2
Net Weight:	330KG
Warranty:	2 years

Distinctive benefits in small sizes

Efficient installation

Savings on electricity bills

Easy management